



Supported truss systems

	QL40A	QD40A	QD30A
Main tubes	Extruded aluminium EN-AW 6082 T6 – Ø50x4	Extruded aluminium EN-AW 6082 T6 – Ø50x3	Extruded aluminium EN-AW 6082 T6 – Ø50x3
Crossways tubes	Extruded aluminium EN-AW 6082 T6 – Ø30x3	Extruded aluminium EN-AW 6082 T6 – Ø30x3	Extruded aluminium EN-AW 6082 T6 – Ø30x3
Connecting system	Aluminium fork EN-AW 6082 T6	Aluminium plate EN-AC 47000	Aluminium plate EN-AC 47000
Max height as a tower [m]	12	9	7,2

Components

Decription	Weight
MTB40 Base in sheet aluminium EN-AW 5083 – 15 mm thickness + 4 stabilizer	166 Kg
MTT40F Top in aluminium alloy EN-AW 6082 T6 with two pulleys	17 Kg
QL40A truss system (approx.)	12,5 Kg/m
QD40A truss system (approx.)	9,5 Kg/m
QD30A truss system (approx.)	8 Kg/m

These technical data are valid only for structures entirely assembled with Litec materials.

Emissione 14/04/2004	LITEC s.r.l. – Via Venier, 52 – 30020 Marcon (VE) www.litectruss.com - info@litectruss.com	LLTCST28GB2 Versione 2
--------------------------------	---	----------------------------------